Model: 10HD7

10 inch monitor

This 10 inch Full HD monitor delivers best-in-class picture quality with excellent 178° viewing angles. The 10 inch monitor has a lightweight housing and is ideal for desktop and wall mounting. The 10HD7 can be connected via HDMI, VGA, BNC or RCA connections.

- 1920 x 1200 resolution (Full HD)
- Input: HDMI, VGA, BNC, RCA
- Mounting: Wall, desktop
- External dimensions: 242 x 169 x 32 mm

© 2024 Beetronics

beetronics

Beetronics
Blanchardstown Corporate Park
Dublin D15 AKK
Ireland

Phone: (01) 903 6425
Fax: (01) 903 6436
E-mail: info@beetronics.ie
Web: www.beetronics.ie

General

Manufacturer	Beetronics
Item number	10HD7
Previous model	10HD6
Product name	10 inch monitor
Warranty	2 years
User manual	Download PDF
Quickstart	Download PDF

Panel

Diagonal size	10.0 inches (254 mm)
Panel type	IPS-LCD
Aspect ratio	16:10 (16:9, 4:3 adjustable)
Response time	10 ms
MTBF	50K
Native resolution	1920 x 1200
Supported resolutions	1920 x 1200 (max), 640 x 480 (min)
Pixels per inch	224 PPI
Backlight	LED
Brightness	300 cd/m2
Contrast	1500:1
Viewing angle	178° horizontal, 178° vertical

© 2024 Beetronics

beetronics

Beetronics
Blanchardstown Corporate Park
Dublin D15 AKK
Ireland

Phone: (01) 903 6425
Fax: (01) 903 6436
E-mail: info@beetronics.ie
Web: www.beetronics.ie

Connectivity

HDMI	1x
VGA	1x
BNC (CVBS)	1x
RCA video	1x
AUX input	1x
AUX output	1x
USB-A	1x integrated USB media player

Size & weight

Colour	Black
Weight	500 grams (900 gram with stand)
Width	242 mm
Height	169 mm
Thickness	32 mm
Display dimensions	216 x 135 mm

Features and functions

Audio	Integrated speakers
Key-lock	The control buttons can be blocked
Auto-on	Automatically powers on when it receives current or a signal
Dimmable	Adjustable backlight brightness
Mirroring	Image can be mirrored, horizontally and vertically
Orientation	Landscape, portrait, face-up
USB media player	The monitor is equipped with a built-in USB media player.

© 2024 Beetronics

beetronics

Beetronics
Blanchardstown Corporate Park
Dublin D15 AKK
Ireland

Phone: (01) 903 6425
Fax: (01) 903 6436
E-mail: info@beetronics.ie
Web: www.beetronics.ie

Power

Input voltage	DC 9-33V
Consumption	5.5 Watt
Power supply	External DC (power adapter included)
Power adapter	Input: AC100-240V, 50/60Hz , Output: 12V-2A
Power adapter output connector	DC barrel plug 2.1mm x 5.5mm

Environmental

Max. non-stop operating time	24/7
Operating temperature	-20°C to +60°C
Storage temperature	-20°C to +70°C
Operating humidity	20% - 80% non-condensing

Mounting

Wall mount	VESA (75 mm)
Flush mount	Possible, no accessories available
Stand	Adjustable and detachable

Certifications & Standards

Certifications	CE, FCC, RoHS, REACH, WEEE, IC, UKCA, e-Mark, EN50155, CCC

Package content

Includes	Monitor, Manual, Remote control, AC power adapter, Stand

© 2024 Beetronics

beetronics

Beetronics
Blanchardstown Corporate Park
Dublin D15 AKK
Ireland

Phone: (01) 903 6425
Fax: (01) 903 6436
E-mail: info@beetronics.ie
Web: www.beetronics.ie

Compatible accessories

Rack mounting	Compatible with 19 inch rack mount kit (RMK2)
Wall mounting	Compatible with flat wall mount bracket (VWB1)
Stand	VDK3 included as standard

© 2024 Beetronics

beetronics

Beetronics
Blanchardstown Corporate Park
Dublin D15 AKK
Ireland

Phone: (01) 903 6425
Fax: (01) 903 6436
E-mail: info@beetronics.ie
Web: www.beetronics.ie