




Model: 10HD7

10 Inch Monitor

This 10 inch Full HD monitor delivers best-in-class picture quality with excellent 178° viewing angles. The 10 inch monitor has a lightweight housing and is ideal for desktop and wall mounting. The 10HD7 can be connected via HDMI, VGA, BNC or RCA connections.

- ✓ Excellent image quality (up to Full HD)
- ✓ Input: HDMI, VGA, BNC, RCA
- ✓ Mounting: Wall, desktop
- ✓ External dimensions: 242 x 168 x 32 mm



General

| | |
|----------------|------------------------------|
| Manufacturer | Beetronics |
| Product line | Monitor Series |
| Product name | 10 Inch Monitor |
| Item number | 10HD7 |
| Previous model | 10HD6 |
| Product type | Monitor |
| Warranty | 2 years |
| User manual | Download PDF |
| Quickstart | Download PDF |

Display architecture

| | |
|-----------------------|------------------------------|
| Diagonal size | 10.1 inches (256 mm) |
| Aspect ratio | 16:10 (16:9, 4:3 adjustable) |
| Native resolution | 1920 x 1200 |
| Pixels per inch | 224 PPI |
| Panel type | IPS-LCD |
| Backlight | LED |
| Surface | Anti-glare hard coating (3H) |
| Supported orientation | Landscape, portrait, face-up |

Display performance

| | |
|-----------------------|------------------------------------|
| Maximum brightness | 300 nits (typical) |
| Minimum brightness | 1 nit |
| Contrast | 1500:1 |
| Viewing angle | 178° horizontal, 178° vertical |
| Response time | 10 ms |
| Supported resolutions | 1920 x 1200 (max), 640 x 480 (min) |

Operational features

| | |
|------------------|--|
| Audio | Dual integrated speakers |
| USB media player | Built-in USB media player with auto-play on power-up and continuous loop playback. Supports common video formats such as: MP4, AVI, MKV, MOV, MPG. |
| Key-lock | The control buttons can be blocked. |
| Auto-on | Automatically powers on when it receives current or a signal. |
| Dimmable | Adjustable backlight brightness via remote control or optional dimmer. |
| Mirroring | Teleprompter compatible. Image can be horizontally and vertically mirrored. |

Connectivity

| | |
|---------------------|--------------------------------|
| HDMI | 1x |
| VGA | 1x |
| BNC (CVBS) | 1x |
| RCA video | 1x |
| USB-A | 1x integrated USB media player |
| AUX input (3.5mm) | 1x |
| AUX output (3.5 mm) | 1x |

Mechanical

| | |
|----------------------------|----------------------------------|
| Dimensions (without stand) | 242 x 168 x 32 mm |
| Image size | 217 x 136 mm |
| Weight | 500 grams (900 grams with stand) |
| Colour | Black |

Mounting

| | |
|---------------------------------|--------------------------------------|
| Wall mount | ✔ VESA 75x75mm |
| Flush mount | ✔ Possible, no accessories available |
| Stand | ✔ Adjustable and detachable |
| Supported mounting orientations | Landscape, portrait, face-up |

Power

| | |
|-------------------------|---|
| Input voltage | 19V DC |
| Operating voltage range | 9-36V DC |
| Power consumption | 9 W (on), 0.4 W (standby) |
| Power supply | External DC power supply included |
| Included power adapter | Input: 100-240V AC, 50/60Hz, Output: 19V DC, 1.5A |
| Power connector | 5.5 mm x 2.1 mm DC barrel connector |
| DC cable length | 1.5 m |
| AC power cord length | 1.0 m |

Environmental

| | |
|------------------------------|--------------------------------|
| Max. non-stop operating time | 24/7 |
| Operating temperature | -10°C to +60°C (14°F to 140°F) |
| Storage temperature | -20°C to +70°C (-4°F to 158°F) |
| Operating humidity | 10% - 90% non-condensing |
| MTBF | 50K |

Compliance & regulations

| | |
|-------------------------|--|
| Regional standards | CE, UKCA, FCC (Part 15), ISED (ICES-003), CCC |
| Environmental standards | RoHS, REACH, WEEE, California Proposition 65, Conflict minerals (3TG; supplier declaration-based) |
| Industry standards | Railway: EN 50155, EN 45545-2; Automotive: e-Mark, UN ECE R10, SAE J1113, SAE J1455 |
| Compliance scope | Standards and certifications apply to the tested product configuration using the specified power supply. Final system-level compliance remains the responsibility of the party responsible for system integration. |
| Compliance statement | Download PDF |

Package content

| | |
|----------|---|
| Includes | Monitor, stand, remote control, power adapter, quickstart |
|----------|---|

Compatible accessories

| | |
|---------------|--|
| Rack mounting | Compatible with 19 inch rack mount kit (RMK2) |
| Wall mounting | Compatible with flat wall mount bracket (VWB1) |
| Stand | VDK3 included as standard |



