





Model: 22HD7M

## 22 Inch Monitor Metal

This 22 inch Full HD monitor delivers best-in-class picture quality with excellent 178° viewing angles. The 22 inch monitor has a sturdy metal housing and is ideal for desktop, flush and wall mounting. The 22HD7M can be connected via HDMI, VGA, BNC or RCA connections.

- ✓ 1920 x 1080 resolution (Full HD)
- ✓ Input: HDMI, VGA, BNC, RCA
- ✓ Mounting: Flush, embedded, wall, desktop
- ✓ External dimensions: 511 x 308 x 40 mm



## General

Manufacturer	Beetronics
Product line	Monitor Series
Product name	22 Inch Monitor Metal
Item number	22HD7M
Previous model	22HDM
Product type	Monitor
Warranty	2 years
User manual	<a href="#">Download PDF</a>
Quickstart	<a href="#">Download PDF</a>

## Display architecture

Diagonal size	21.6 inches (549 mm)
Aspect ratio	16:9 (4:3 adjustable)
Native resolution	1920 x 1080
Pixels per inch	102 PPI
Panel type	IPS-LCD
Backlight	LED
Surface	Anti-glare hard coating (3H)
Supported orientation	Landscape, portrait, face-up

## Display performance

Maximum brightness	350 nits (typical)
Minimum brightness	1 nit
Contrast	3000:1
Viewing angle	178° horizontal, 178° vertical
Response time	10 ms
Supported resolutions	1920 x 1080 (max), 640 x 480 (min)
Color encoding system	PAL/NTSC/SECAM

## Operational features

Audio	Dual integrated speakers
USB media player	Built-in USB media player with auto-play on power-up and continuous loop playback. Supports common video formats such as: MP4, AVI, MKV, MOV, MPG.
Key-lock	The control buttons can be blocked.
Auto-on	Automatically powers on when it receives current or a signal.
Dimmable	Adjustable backlight brightness via remote control or optional dimmer.
Mirroring	Teleprompter compatible. Image can be horizontally and vertically mirrored.

## Connectivity

HDMI	1x
VGA	1x
BNC (CVBS)	1x
RCA video	1x
USB-A	1x integrated USB media player
AUX input (3.5mm)	1x
AUX output (3.5 mm)	1x

## Mechanical

Dimensions (without stand)	511 x 308 x 40 mm
Image size	478 x 269 mm
Weight	4300 grams (5200 grams with stand)
Colour	Black
Thickness	41 mm

## Mounting

Wall mount	<input checked="" type="checkbox"/> VESA 100x100mm
Flush mount	<input checked="" type="checkbox"/> Mounting strips included
Stand	<input checked="" type="checkbox"/> Adjustable and detachable
Supported mounting orientations	Landscape, portrait, face-up

## Power

Input voltage	DC 10-36V
Consumption	22 W (on), 0.4 W (standby)
Power supply	External DC (power adapter included)
Power adapter	Input: AC100-240V, 50/60Hz , Output: 19V-2.5A
Power adapter output connector	DC barrel plug 2.1mm x 5.5mm

## Environmental

Max. non-stop operating time	24/7
Operating temperature	-10°C to +60°C (14°F to 140°F)
Storage temperature	-20°C to +70°C (-4°F to 158°F)
Operating humidity	10% - 90% non-condensing
MTBF	50K

## Compliance & regulations

Regional standards	CE, UKCA, FCC (Part 15), ISED (ICES-003), CCC
Environmental standards	RoHS, REACH, WEEE, California Proposition 65, Conflict minerals (3TG; supplier declaration-based)
Industry standards	Maritime: IEC 60945, DNV-CG-0339 (requires BEE-PSU1-MAR); Railway: EN 50155, EN 45545-2; Automotive: e-Mark, UN ECE R10, SAE J1113, SAE J1455; Medical: EN 60601-1, EN 60601-1-2 (requires BEE-PSU1-MED)
Compliance scope	Standards and certifications apply to the tested product configuration using the specified power supply. Final system-level compliance remains the responsibility of the party responsible for system integration.
Compliance statement	<a href="#">Download PDF</a>

## Package content

Includes	Monitor, mounting strips, stand, remote control, power adapter, quickstart
----------	--

## Compatible accessories

Dimmer	<a href="#">Compatible with external dimmer (DMK7/DMK8)</a>
Wall mounting	<a href="#">Compatible with flat wall mount bracket (VWB1)</a>
Stand	<a href="#">Compatible with VDK7 metal stand</a>



