




Model: 10TS7M

## 10 Inch Touchscreen Metal

This Full HD 10 inch touchscreen has a reliable multi-touch panel which ensures accurate operation. The 10TS7M delivers best-in-class picture quality with excellent 178° viewing angles and is compatible with Windows, Mac & Linux operating systems. The touchscreen monitor is designed for professional applications, easy to integrate and suitable for intensive use.

- ✓ Full HD multi-touch panel
- ✓ Input: HDMI, DisplayPort, USB-C, VGA
- ✓ Mounting: Flush, embedded, wall, desktop
- ✓ External dimensions: 249 x 170 x 40 mm



## General

Manufacturer	Beetronics
Product line	Touchscreen Series
Product name	10 Inch Touchscreen Metal
Item number	10TS7M
Previous model	10TS5M
Product type	Touchscreen
Warranty	2 years
User manual	<a href="#">Download PDF</a>
Quickstart	<a href="#">Download PDF</a>

## Display architecture

Aspect ratio	16:10 (16:9, 4:3 adjustable)
Native resolution	1920 x 1200
Pixels per inch	224 PPI
Panel type	IPS-LCD
Backlight	LED
Surface	Tempered glass
Supported orientation	Landscape, portrait, face-up

## Display performance

Maximum brightness	300 nits (typical)
Minimum brightness	1 nit
Contrast	1500:1
Viewing angle	178° horizontal, 178° vertical
Response time	10 ms
Supported resolutions	1920 x 1200 (max), 640 x 480 (min)

## Touch technology

Touch technology	Capacitive (PCAP)
Touch points	10-point (multi-touch)
Touch interface	USB HID-compliant
Touch control	Stylus, hand, glove
Gesture support	Tap, swipe, scroll, pinch-to-zoom (dependent on host system OS and application)

## Operational features

Audio	Dual integrated speakers
Key-lock	The control buttons can be blocked.
Auto-on	Automatically powers on when it receives current or a signal.
Dimmable	Adjustable backlight brightness via remote control or optional dimmer.

## Software & compatibility

Windows	Windows 8, 10, 11
Windows Embedded	Windows Embedded 8 Industry, 8.1 Industry, IoT Enterprise
macOS	Tahoe, Sequoia, Sonoma
Linux	All Linux distributions
Brightsign	All BrightsignOS versions
Samsung DeX	All Samsung DeX versions

## Connectivity

HDMI	1x
DisplayPort	1x
VGA	1x
USB-C	1x Video, audio, touch
USB-A	Via USB-C to USB-A adapter. This only activates the touch functionality and should be combined with HDMI, the DisplayPort, or VGA for image display.
AUX input (3.5mm)	1x
AUX output (3.5 mm)	1x

## Mechanical

Dimensions (without stand)	249 x 170 x 40 mm
Active area	237 x 158 mm
Weight	1350 grams (1750 grams with stand)
Colour	Black

## Mounting

Wall mount	✔ VESA 75x75mm
Flush mount	✔ Mounting strips included
Stand	✔ Adjustable and detachable
Supported mounting orientations	Landscape, portrait, face-up

## Power

Input voltage	DC 9-36V
Consumption	11 W (on), 0.4 W (standby)
Power supply	External DC (power adapter included)
Power adapter	Input: AC100-240V, 50/60Hz , Output: 19V-1.5A
Power adapter output connector	DC barrel plug 2.1mm x 5.5mm

## Environmental

Max. non-stop operating time	24/7
Operating temperature	-10°C to +60°C (14°F to 140°F)
Storage temperature	-20°C to +70°C (-4°F to 158°F)
Operating humidity	10% - 90% non-condensing
Ingress protection (IP)	IP65 front panel
Impact protection (IK)	IK08
MTBF	50K

## Compliance & regulations

Regional standards	CE, UKCA, FCC (Part 15), ISED (ICES-003), CCC
Environmental standards	RoHS, REACH, WEEE, California Proposition 65, Conflict minerals (3TG; supplier declaration-based)
Industry standards	Maritime: IEC 60945, DNV-CG-0339 (requires BEE-PSU1-MAR); Railway: EN 50155, EN 45545-2; Automotive: e-Mark, UN ECE R10, SAE J1113, SAE J1455; Medical: EN 60601-1, EN 60601-1-2 (requires BEE-PSU1-MED)
Compliance scope	Standards and certifications apply to the tested product configuration using the specified power supply. Final system-level compliance remains the responsibility of the party responsible for system integration.
Compliance statement	<a href="#">Download PDF</a>

## Package content

Includes	Touchscreen, USB-C to USB-C cable, USB-C to USB-A cable, mounting strips, stand, remote control, power adapter, quickstart
----------	--

## Compatible accessories

Infrared extension	<a href="#">Compatible with infrared extender (IRC7)</a>
Dimmer	<a href="#">Compatible with external dimmer (DMK7/DMK8)</a>
Rack mounting	<a href="#">Compatible with 19 inch rack mount kit (RMK2)</a>
Wall mounting	<a href="#">Compatible with flat wall mount bracket (VWB1)</a>
Stand	VDK3 included as standard
Touch pen	<a href="#">Compatible with CTS7 capacitive touchscreen stylus</a>



